




2 part epoxy paint HEMPEL - HEMPADUR 45141 / 45143



| | |
|------------------------------|---|
| Article no.: | 3616 |
| Machine no.: | |
| Type: | HEMPADUR 45141 / 45143 |
| Year of construction: | |
| Price: | €175.00 |
| Description: | 23 bundles of 20 litres each (15 litres of paint + 5 litres of hardener) colour white (similar to RAL 9003) two-component polyamid adduct hardened epoxy colour self-priming minimum durability until 09 / 2024 weight approx. 28 kg / bundle - price per bundle - good resistance against abrasion and shock, but also against seawater, mineral oils, aliphatic hydrocarbons and splashes of petrol, |



Maschinenlager
Werftstraße 17-46
32423 Minden

Tel: +49 (0)571 / 388 13 65
Fax: +49 (0)571 / 388 13 66
Mobil: +49 (0)171 / 998 02 44
E-Mail: info@jens-heydn.de



www.jens-heydn.de

kerosene, lubricating oils and similar products.

harmless in conjunction with grain cargo.

Recommended use: 1. As thick layer primer, intermediate and/or final coat in coating systems for (heavy) protection against corrosion according to specification. (As final coating if cosmetic appearance is of lesser importance.) 2. For repairs and maintenance work at temperatures of more than -10°C on hatch covers, decks, in cargo holds etc. Decks, in Laderäumen usw. 3. As ballast tank coating. Yield : approx. 4.0 m²/l at a layer thickness of 150 µm (micrometers). Dry times: dust-dry: approx. 4 hours at 20°C (ISO 1517) approx. 5 hours at +5°C (ISO 1517) hand-dry: approx. 7 hours at 20°C approx. 11 hours at +5°C through-hardened: 7 days at 20°C 20 days at +5°C